

C501



- Haute protection / High isolation
- Petit boîtier / Small outline

C503



- Petit boîtier / Small outline
- Boîtier zamac / Zamac housing



C504

- Coupleur TV/SAT pour LNB Twin
- TV/SAT combiner for TWIN LNB

C505



- Haute protection / High isolation
- Boîtier zamac / Zamac housing



C502

- Haute protection / High isolation
- Boîtier étanche / Weatherproof housing

Spécifications / Specifications	C501	C502	C503	C505	C504
Fréquence (satellite) / Frequency range (SAT)	950 - 2150 MHz				2 x 950-2150 MHz
Fréquence (terrestre) / Frequency range (terr.)	5-862 MHz				2 x 5-790 MHz
Passage cc(terr./SAT) / DC pass (terr./SAT)	non - no / oui - yes				
Pertes (satellite) / Insertion loss (SAT)	< 3 dB	< 3 dB	< 3 dB	< 3 dB	< 3 dB
Pertes (terrestre) / Insertion loss (terrestrial)	< 2 dB	< 2 dB	< 2 dB	< 2 dB	< 5.5 dB
Protection (SAT/terr) / Isolation (SAT/terr)	> 40 dB	> 40 dB	> 30 dB	> 40 dB	> 40 dB
Protection (terr/SAT) / Isolation (terr/SAT)	> 30 dB	> 30 dB	> 18 dB	> 30 dB	> 30 dB
Code	1501	1502	1503	1505	1504
EAN code	5420037615018	5420037615025	5420037615032	5420037615056	5420037615049
Poids / Weight	0.080	0.18	0.052	0.18	0.20