

- ◇ Transform two HDMI sources into a RF - DVBT signal, ready to distribute over your coaxial network.
- ◇ Both programs on one DVBT channel
- ◇ USB input allows you to replace one input to play .ts files over DVBT network
- ◇ Play out sequential files (file001, file002, file003....)
- ◇ Record your input to USB
- ◇ **Full digital signage using TMHDIface and internal clock**
- ◇ RF Bypass
- ◇ Ergonomic quick and advanced menu using 3 buttons and 2x16 character LCD.



TECHNICAL SPECIFICATIONS:

Video input (x2)	Input	HDMI
	Resolution modes	480p -576p -720p - 1080i - 1080P
	Compression	H.264 – bitrate 5-15 Mb/s
Audio input	Input	HDMI
	Sample Rate	HDMI (32kHz / 44.1 kHz / 48 kHz)
	Compression	AAC-LC / MPEG1-L2– bitrate 128-320 Kb/s
DVB Processing	Table insertion	PAT, PMT, SDT, NIT
	Configuration	Channel/network name, SID, LCN, TSID, ONID, NID, versions, audio, video PIDs...
DVB-T output	Output frequency / level	170-230 MHz + 470-862 MHz / > 85 dBμV
	Constellation - FEC	QPSK/16QAM/64QAM - 1/2, 2/3, 3/4, 5/6, 7/8
	Guard interval	1/4, 1/8, 1/16, 1/32
	Mode - MER	2K/8K - 33 dB
Power	DC 2.1 mm connector	+5V
	Consumption	10 Watts
Dimensions	LxWxH	150x130x35mm
	Weight	0.9 kg
EAN code	TM2HD	5420037690022

Product designed and produced in Belgium