

- ◇ Transform your HDMI source into a RF - DVBT signal, ready to distribute over your coaxial network.
- ◇ Resolutions up to 1080P
- ◇ HDMI loop keeps your HDMI output from your source available
- ◇ RF Bypass
- ◇ Ergonomic quick and advanced menu using 3 buttons and 2x16 character LCD.
- ◇ Fast programming using PC and TMHDIface



## TECHNICAL SPECIFICATIONS:

<b>Video input</b>	Input	HDMI
	Resolution modes	480p -576p -720p - 1080i - 1080P
	Compression	H.264 – bitrate 5-15 Mb/s
<b>Audio input</b>	Input	HDMI
	Sample Rate	HDMI (32kHz / 44.1 kHz / 48 kHz)
	Compression	AAC-LC / MPEG1-L2– bitrate 128-320 Kb/s
<b>DVB Processing</b>	Table insertion	PAT, PMT, SDT, NIT
	Configuration	Channel/network name, SID, LCN, TSID, ONID, NID, versions, audio, video PIDs...
<b>DVB-T output</b>	Output frequency / level	170-230 MHz + 470-862 MHz / > 85 dBμV
	Constellation - FEC	QPSK/16QAM/64QAM - 1/2, 2/3, 3/4, 5/6, 7/8
	Guard interval	1/4, 1/8, 1/16, 1/32
	Mode - MER	2K/8K - 33 dB
<b>Power</b>	DC 2.1 mm connector	+5V
	Consumption	10 Watts
<b>Dimensions</b>	LxWxH	150x130x35mm
	Weight	0.9 kg
<b>EAN code</b>	TM170HD	5420037691708

Product designed and produced in Belgium